

RSVR/RTVR-Series

Package: SIL3/SMD-DIL10

Current: 0,5 ~ 2A



R-Series model	Load	Package	Regulated?	Input voltages	Output voltages	Output type	Isolation voltage	
RSVR-78Myy	0.5A	SIL3	Yes	4.75-34	1.5/1.8/2.5/3.3/5/7.2/9/12/15	Single	non-isolated	
RSVR-78Myyv2	0.5A	SIL3	Yes	4.50-28	3.3/5/12/15	Single	non-isolated	
RSVR-78Myyv3	0.5A	SIL3	Yes	4.75-36	3.3/5/-5/9/12/-12/15/-15	Single	non-isolated	
RSVR-78Wyy	0.5A	SIL3	Yes	9.00-72	3.3/5/6.5/7.2/9/12/15	Single	non-isolated	
RSVR-78FyyAv2	1.0A	SIL3	Yes	7.00-28	3.3/5	Single	non-isolated	
RSVR-78FyyDv3	1.0A	SIL3	Yes	6.00-36	3.3/5/-5/9/12/-12/15/-15	Single	non-isolated	
RSVR-78DyyDv3	2.0A	SIL3	Yes	4.75-18	1.5/1.8/2.5/3.3/5/6.5	Single	non-isolated	
RTVR-78MyyDv3	0.5A	DIL10 SMD (8p)	Yes	4.75-36	1.5/1.8/2.5/3.3/5/6.5/9/12/15 (adjustable)	Single	non-isolated	
RTVR-78FyyDv3	1.0A	DIL10 SMD (8p)	Yes	4.75-36	1.5/1.8/2.5/3.3/5/6.5/9/12 (adjustable)	Single	non-isolated	

All specifications typical at TA = 25 °C, nominal input voltage and full load unless otherwise specified.
The information and specification contained in this data sheet are believed to be correct at time of publication.
However RSG accepts no responsibility for consequences arising from printing errors or inaccuracies.
Specifications are subject to change without notice.