

Item # P10188-08, Multi-Set (4-Types: V-Pin, ST, SMA, and F07) Insertion Loss Test Kit

OFS' HCS® fiber family of 50, 62.5, 200, and 400 µm fibers, cables and components are compatible with these test kits. They measure insertion loss across the fiber sizes below and the connector types listed. Each kit includes the corresponding launch jumpers for those cabled connector combinations it measures. Kits are available for single connector and cable types and sizes or for certain preselected combinations.



[Specifications](#) · [Optical Properties](#) · [General Properties](#) · [Ordering Information](#)

Specifications

Size	200 µm
------	--------

Optical Properties

Detector Type	Silicon (Si)
Calibrated Wavelengths	660 nm 850 nm
Accuracy (@ 25°C and -10 dB/m)	± 0.25 dB
Resolution	0.01 dB

General Properties

Operating Temperature	0 to +50 °C
Storage Temperature	-30 to +60 °C
Relative Humidity	0 to 95% (non-condensing)
Product Dimensions (H x W x D)	5.5 x 3.2 x 1.5 in
Case Dimensions (H x W x D)	4.0 x 13.5 x 9.5 in
Connector Interface	Multi-Set (4-Types: V-Pin, ST, SMA, and F07)
Battery Life	60 hours typical with 9V alkaline

Ordering Information

Order From Location	AVON LOCATION (headquarters) 1.888.438.9936 toll-free in the United States and Canada 1.860.678.0371 for all other locations 55 Darling Drive Avon, CT 06001, USA info@SpecialtyPhotonics.com
Order By Item #	P10188-08